

# LTRN036NW

Illuminatore circolare a LED, diametro interno 61 mm, luce diretta, bianca

## CARATTERISTICHE

### Specifiche ottiche

Colore luce, lunghezza d'onda di picco		white
Optimal working distance	(mm)	65-240
Illuminance at minimum working distance	(lux)	15900
Illuminance at maximum working distance	(lux)	3750

### Lighting area diameter

Outer	(mm)	143
Inner	(mm)	84

### Specifiche elettriche

Number of LED rows		1
--------------------	--	---

### Continuous mode <sup>1</sup>

Supply voltage	(V)	24
Current	(mA)	840
Power consumption	W	20.16

### Pulsed mode

Supply voltage <sup>2</sup>	(V)	24-48
Max pulse current <sup>3</sup>	(mA)	2000
Max. trigger pulse duration	(ms)	10
Duty cycle	(%)	0-10%

### Specifiche meccaniche

Diametro esterno	(mm)	157
Diametro interno	(mm)	61
Altezza	(mm)	40
Massa	(g)	560
Cooling method	Attached to machine part for better heat dissipation	

### Compatibilità

Prodotti compatibili	TCxx036, TCxM036, TC16M036, TCSM036, MCZRxxx-yyy
----------------------	--

## NOTE

1. Longevità: 20.000 ore (calo di intensità del 50%) a 25° C
2. Raccomandata a 36 V.
3. A corrente di pilotaggio costante

